

# On the allowance for support costs in Prager-Rozvany' optimal layout theory

Mariano Vázquez Espí

Received: date / Accepted: date

**Abstract** A recent study by Rozvany and Sokół discussed an important topic in structural design: the allowance for support costs in the optimization process. This paper examines a frequently used kind of support—that of simple foundation with horizontal reaction by friction—that appears not covered for the Authors' approach. A simple example is examined to illustrate the case and to try of applying the Authors' method; also some solutions from standard design method are included.

**Keywords** Support cost · Michell trusses · fixed boundary problems · free loading problems

## 1 Introduction

The fixed boundary class of problems was exactly defined by Cox (1965:116-117), as a different class of problems than those covered by Maxwell & Michell design theory. In his remarkable book, Cox shown that although the theories to tackle with these two classes have different optimality criteria, both they lead to optimal layouts on the basis of Hencky-Prandtl nets (1965:96). The optimality criteria for the former class was after formulated by Hemp (1973) in detailed form and by many other authors.

The fixed boundary theory has a well-known drawback: “the reactions such as those at [fixed supports], are in any case carried by some other bodies acting as structures and the true picture of the economy achieved should include the abutments.” (Owen, 1965:64). A conspicuous extension of this theory for the allowance of

support cost has been derived by Rozvany and Sokół (2012:§3–7) from the optimal layout theory of Prager and Rozvany (1977), “which is based on ‘optimal plastic design’” of Prager and Shield (1967). It could hope that with this extension the shortcoming noted by Cox and Owen could be filled.

## 2 Foundation with friction

The frequently used foundation with friction (see e.g. Bow, 1873) is composed by a prismatic body with square base  $A = a \times a$  and height  $h$ . For an allowable soil stress  $\sigma_S$ ,  $A = |Y|/\sigma_S$ , being  $Y$  the vertical reaction to be exerted to the structure by the foundation (see Fig. 1a). If the static friction coefficient between foundation and soil is  $\mu$ , the foundation can bear too an horizontal reaction  $X$  such that  $|X| \leq -\mu Y$  providing  $Y \leq 0$  accordingly with the sign convention of Fig. 1 of Rozvany and Sokół (2012), i.e., the soil under the foundation will be compressed under  $Y$ -action. For a given foundation material, the total volume of the foundation can be expressed as  $\lambda a^3$ , being  $\lambda$  a given constant dependent of foundation material and soil properties. Let us select the foundation volume as the cost following Authors', then the function costs can be expressed as follows:

$$C(Y) = \begin{cases} \lambda \left( \frac{-Y}{\sigma_S} \right)^{\frac{3}{2}} & \text{if } Y \leq 0 \\ \infty & \text{if } Y > 0 \end{cases} \quad (1)$$

$$C(X) = \begin{cases} 0 & \text{if } Y \leq 0 \text{ and } |X| \leq -\mu Y \\ \infty & \text{if } Y > 0 \text{ or } |X| > -\mu Y \end{cases} \quad (2)$$



Once we have one Maxwell's problem, we can search for the optimal layout that minimise the Michell's functional, the "quantity" of structure  $\mathcal{V}$  (1904:Eq. (3)). We can compute as an alternative the volume of the structure—to remain within Authors' realm—with the well-known formula (Cox, 1965:87, Eq. (121); Owen, 1965:53, Eq. (18); Barnett, 1966:20, Eq. (5)):

$$V = \frac{1}{2} \left\{ \left( \frac{1}{P} + \frac{1}{Q} \right) \cdot \mathcal{V} + \left( \frac{1}{P} - \frac{1}{Q} \right) \cdot C \right\} \quad (4)$$

where—following Michell's notation— $P, Q$  are the allowable stresses in tension and compression, respectively; and  $C$  is the "static constant" of Owen (1965)—see Michell (1904:Eq. (1)):  $C = -\frac{1}{2}PL(1 + \mu)$  in this example. Notice that in doing so we do not account any cost for vertical and horizontal reactions because these reactions are invariable—their cost are constant and finite for all the solutions in the search space. Of course, once a solution is selected as the appropriated one, the designer adds to the cost of the structure the cost of the foundations.

It should be noted too that the optimal layout will be independent of  $P, Q$  for any given  $\mu$ —but, nevertheless, volume varies as indicated by (4). This fact is important and its proof is simple. Let us consider the variation of  $V$  within the feasible solution space:

$$\delta V = \frac{1}{2} \left( \frac{1}{P} + \frac{1}{Q} \right) \cdot \delta \mathcal{V} \quad (5)$$

as  $\delta C = 0$ . Hence  $\forall P, Q : \delta V = 0 \Leftrightarrow \delta \mathcal{V} = 0$  and any optimal layout for  $\mathcal{V}$  will be optimal too for  $V$  for any  $P, Q$  couple.

The non-optimal solutions in Fig. 1 were obtained by a simulated annealing code (Vázquez Espí, 1995). All they suggest the existence of Michell solutions that fulfil his second theorem. These solutions seem to correspond to a fan CDE (a **T**-region following Authors'), and a region EDB, see Fig. 1a. The latter will be composed of a **T**-region (EDFG) and a **R**-region (GFB). With  $\mu = 0$ , GFB area leads to zero; on the other hand CDE and EDFG areas will be zero with  $\mu = 1$ . With this hypothesis, the internal force in the arch CDFB will be constant and equal to  $N_{\text{CDFB}} = P\sqrt{1 + \mu^2}/2$  and the angle of the arch in B with the vertical direction will be exactly  $\arctan \mu$ . The angle of the fan can then be obtained by elementary equilibrium calculations, and the frontier GF would be obtained by the minimum condition on  $\mathcal{V}$ . The dashed-lines in Fig. 1 represents the first part of these calculus.

It should be stressed that when a given optimal design—completely defined—will be analysed with any standard, suitable code, the Michell virtual displacement field will not be obtained, because the difference between this field and the actual field of the designed

structure: in the latter the horizontal displacement of foundations is non-linear in respect to its contact with the ground—including a perfect rigid one—the yield tension strain can be different than that of the compression—e.g., because difference in Young's Modulus yet when allowable stresses have equal value—or the self-weight of both structure and foundations have to be accounted, etc. This fact is a consequence of the static approach of Maxwell and Michell ("free loading" without *any* kinematic support conditions): the displacement fields used in the theory are *virtual* ones ever, and that of the Michell's theorems is only required to be of bounded absolute strain and continuous.

This point is a key one to formulate any design theory, and it is worth of further analysis. The design problem with an unique load conditions is defined by given useful loads and some planes for support the structure (e.g., the soil plane for a standard building). Accordingly with Hemp (1958:1), "The theory [of structural design] ought to be in a position to tackle the design problem directly, that is, to begin with the given forces and to produce by calculation the best structure that will safely carry them". The first pass in the designing process is to look for some appropriate shapes. As at this very time the designer has not selected any structural material, the theory must be formulated without any constitutive equations. Moreover, the designers neither has any structure to be analysed, hence it makes no sense to use structural analysis models as rolled or pinned supports. The outstanding merit of Maxwell in 1870 was to formulate his design theory only with equilibrium equations so it could be useful for the designer. And the equal remarkable improvement of Michell was to use the compatibility equations only to derive his optimality criterion on optimal solutions for Maxwell's problems, being respectful with Maxwell's fundamental axioms.

## 5 Conclusion

The case of simple foundations with friction has solution within the standard design theory of Maxwell & Michell—the "free loading" of Cox—, but it is not obvious that it can be tackled with the method proposed by the Authors.

The Writer will be grateful to the Authors for further comments and criticism.

## References

- Ralph L. Barnett. Survey of Optimum Structural Design. *Experimental Mechanics*, 6(12):19A–26A, December 1966.

- Robert H. Bow. *Economics of Construction in relation to Framed Structures*. E. & F. N. Spon, London, 1873.
- Jaime Cervera Bravo. *Concebir y analizar estructuras*. Universidad Politécnica de Madrid, Madrid, 2008. URL <http://oa.upm.es/189/>. 222 pp.
- H. L. Cox. *The design of structures of least weight*. Pergamon, Oxford, 1965.
- WS Hemp. Theory of structural design. Report 214, North Atlantic Treaty Organization, Advisory Group for Aeronautical Research & Development, Palais de Chaillot, Paris, 1958.
- WS Hemp. *Optimum structures*. Clarendon, Oxford, 1973.
- Anthony George Maldon Michell. The Limits of Economy of Material in Frame-structures. *Philosophical Magazine S.6*, 8(47):589–597, 1904. also available at <http://habitat.aq.upm.es/gi/mve/dt/>.
- J. B. B. Owen. *The Analysis and Design of Light Structures*. Edward Arnold (publishers) Ltd., London, 1965.
- W. Prager and G.I.N. Rozvany. Optimization of Structural Geometry. In A.R. Bednarek and L. Cesari, editors, *International Symposium on Dynamical Systems*, pages 265–293, New York, 1977. University of Florida, Academic Press Inc.
- W. Prager and R. T. Shield. A General Theory of Optimal Plastic Design. *Transactions of the ASME—Journal of Applied Mechanics*, pages 184–186, March 1967.
- George I. N. Rozvany. *Optimal design of flexural systems*. Pergamon, London, 1976.
- George I. N. Rozvany and T. Sokół. Exact truss topology optimization: allowance for support costs and different permissible stresses in tension and compression — extensions of a classical solution by Michell. *Structural and Multidisciplinary Optimization*, 2012. doi: 10.1007/s00158-011-0736-6.
- Mariano Vázquez Espí. Un nuevo algoritmo para la optimización de estructuras: el recocido simulado. *Informes de la Construcción*, 46(436):49–69, 1995. doi: 10.3989/ic.1995.v46.i436.1084.